

INDUSTRIAL SOURCING SOLUTIONS CO

IP67

IP65

IP65

LED

#### (SCANGRIP" Work Lamp

Description:

Sturdy LED work lights with shock-resistant aluminium casing and rubber protective surround.

- Soft non-shadowing anti-glare lamp, with low heat emission.
- High light output, low energy consumption, long working life.
- Certified for exterior use and for use in humid environments

NOVA work lamps with integral carrying handle. High-performance COB-LED with 5-step dimmer function, pivoting.

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Article No.	Power(W)	Illumination	Siz (LxWxH)	Weight
#S#10894	26	300-3000	235x88x233	2380g
#S#10895	42	500-5000	267x87x262	2660g
#S#10896	84	1000-10000	302x102x298	4100g



Description:

Sturdy LED work lights with shock-resistant aluminium casing and rubber protective surround.

- Soft non-shadowing anti-glare lamp, with low heat emission.

- High light output, low energy consumption, long working life.

- Certified for exterior use and for use in humid environments.

Compact work lamp, including battery charger.

SMD-LED work lights with frosted glass lens for homogeneous and pleasant illumination.

IP65: Protected against jets of water from all directions and protected against penetration by dust

(dust-tight), also completely protected against touching.



#S#10897 20 1600 202x202x55 8 A.h 7.4V 1450g	Article No.	Power(W)	Illumination	Siz (LxWxH)	Battery Capacity	Battery Voltage	Weight
		20	1600		8 A.h	7.4V	1450g

#### (SCANGRIP

#### Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

**Rechargeable Work Lamp - Miniform** 

Miniform version, slim, handy size for the pocket (120×59×25 mm), belt clip, ergonomic handle. High-performance COB LED technology for extremely bright homogeneous lighting of an area at two levels of brightness.

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Supplied with charger and USB cable.

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Working Life Stage 2
#S#12808	200 / 100	1.6 A.h	3.7V	138g	2.5h	5h

#### (SCANGRIP

## **Rechargeable Work Lamp - Uniform**

Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

New generation of the version UNIFORM. Extremely sturdy, with intelligent battery charge display and additional spotlight. Belt clip.

High-performance COB LED technology for extremely bright homogeneous lighting of an area at two levels of brightness.

IP65: Protected against jets of water from all directions and protected against penetration by dust

(dust-tight), also completely protected against touching.

Supplied with charger and USB cable.

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Working Life Stage 2	Size (mm)
#S#06432	500 / 250	3 A.h	3.7V	265g	3h	6h	190L x 60W

#### IP Index of Protection to EN 60529 (IP → Index of Protection)

#### 1. Index

#### Degree of protection against foreign bodies and dust

IP 4.. Protected against penetration by solid foreign bodies  $\geq$  1mm.

IP 5.. Protection against harmful dust deposits (dust protected).

IP 6.. Protection against penetration by dust (dust-tight).

## 2. Index

#### Degree of protection against water

IP .. 0 No protection.

- IP .. 2 Protection against dripping water at up to 15° angle to the casing.
- IP .. 4 Protection against sprayed water from all directions.
- IP .. 5 Protection against jets of water from all directions.
- IP .. 6 Protection against strong jets of water from all directions.
- IP .. 7 Protection against intermittent immersion in water





LED

INDUSTRIAL SOURCING SOLUTIONS CO.

MY INDUSTRIAL SOLUTION ENT.

## LAMPS & ELECTRICAL ACCESSORIES

# Rechargeable Work Lamp - Mini-Pro

Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

New generation of the MINI-MAG version, powerful spotlight and main light, with charge indicator at the front.

High-performance COB LED technology for extremely bright homogeneous lighting of an area at two levels of brightness. Steplessly dimmable.

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching. Supplied with USB charging cable.

#S#12809 20-200 1.2 A.h 3.7V 143g 2-20h 202L x 40W	Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
	#S#12809	20-200			143g	2-20h	202L x 40W

#### **(**SCANGRIP<sup>®</sup>

Rechargeable Work Lamp - MAG

Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

IP20: Protected against penetration by foreign bodies with  $\emptyset$  < 12 mm, however touching should be avoided, and offers no protection against water. Supplied with charger and USB cable.



IP54

IP20

IP54

IP20

LED

LED

LED

LED

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
#S#12810	300 / 150	2.2 A.h	3.7V	273g	2.5h / 5h	260L x 61W

#### (SCANGRIP

Rechargeable Work Lamp - MAG-PRO Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

New generation of the MAG3 version, with exceptionally high light output, very powerful spotlight and main light, with charge indicator at the front.

High-performance COB LED technology for extremely bright homogeneous lighting of an area at two levels of brightness. Steplessly dimmable.

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching. Supplied with charger and USB cable.

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
#S#12811	60-600	2.6 A.h	3.7V	312g	1.5-15h	270L x 70W

#### (SCANGRIP Rechargeable Work Lamp - STAR

#### Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

Handy cordless work lamp and floodlight combined in a single lamp. Flexible handle with built-in magnet, suitable for direct mounting on a Scangrip stand. Built-in power bank with USB socket. Without suspension hook.

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with charger and USB cable.

IP65	LED	
CICANSHIP		

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
#S#06433	1000 / 500	5.2 A.h	3.7V	710g	2.5 / 5h	156L x 103W

#### (SCANGRIP

Description:

LED cordless work lamp with high-power LEDs for high light output. With fold-out swivel support hook and powerful attachment magnet.

**Rechargeable Pencil Work Light - MAGPEN3** 

Steplessly dimmable. Powerful general-purpose LED rechargeable battery torch with side main beam and torch head

spotlight. With pocket clip and integral magnet.

IP20: Protected against penetration by foreign bodies with  $\emptyset < 12$  mm, however touching should be avoided, and offers no protection against water.

Supplied with USB charging cable.

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
#S#12812	15-150	0.75 A.h	3.7V	98g	2-20h	174L



SCANGRIP



SOURCING SOLUTIONS

INDUSTRIAL



Article No.	Illumination	Battery Voltage	Weight	Working Life	Size (mm)	
#S#12815	120-500	3.7V	250g	2.5h	380L	

INDUSTRIAL SOURCING SOLUTIONS CO

Supplied with USB charging cable.

## LAMPS & ELECTRICAL ACCESSORIES

## HOLEX

#### **Rechargeable Pen Light**

Description: LED rechargeable pen light with main beam and spotlight, with a pocket clip with powerful attachment magnet. Magnetic base with 360° rotation. IP20: Protected against penetration by foreign bodies with ø < 12 mm, however touching should be avoided, and offers no protection against water.



LED

IP20

IP65

IP30

LED

LED

ATEX

Article No.	Illumination	Battery Capacity	Battery Voltage	Weight	Working Life	Size (mm)
#S#12817	220 / 80	1.1 A.h	3.7V	83g	2.5h	170L x 20W

#### (SCANGRIP

#### **Rechargeable EX Work Light**

IP65 LED ATEX Description: Explosion-proof work lamp, tested to the applicable ATEX guidelines. Extremely bright illumination and very long working life. Rechargeable multi-function LED EX work light. Main lamp with two-stage switch and upper spotlight. IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Supplied with charging station. Article No. Illumination Battery Capacity **Battery Voltage** Weight Working Life Size (mm) #S#12818 150 / 290 2.8 A.h 3.2V 220Lx70Wx39H 420g 6/3h

#### **(**SCANGRIP **EX Work Light**

Description:

xplosion-proof work lamp, tested to the applicable ATEX guidelines. Extremely bright illumination and very long working life. Strong and sturdy Ex-protected work lamp. IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Standard: Certified for ATEX zones: Approved and certified for gas 1 and 2, dust 21 and 22. ATEX directive No. 2014/34/EU, IEC and IECEx. Supplied with 10 m cable, Schuko plug, 100 - 240 V 50/60 Hz, 23 W.

Article No.	Power(W)	Illumination	Siz (LxWxH)	Weight
#S#12819	23	1000 / 2000	270x266x123	4000g

#### (SCANGRIP

## **Rechargeable EX Work Light**

Description: Explosion-proof work lamp, tested to the applicable ATEX guidelines. Extremely bright illumination and very long working life. Sturdy and robust cordless LED EX work light. Certified for ATEX zones: Approved and certified for gas 1 and 2, dust 21 and 22. ATEX directive No. 2014/34/EU, IEC and IECEx. Supplied with 5 m charging cable.

IP65 LED ATEX

Article No.	Illumination	Siz (LxWxH)	Weight	Battery Capacity	Battery Voltage	Working Life
#S#12820	1500 / 750	270x266x123	3900g	1.4 A.h	19.2V	2 / 4h

#### (SCANGRIP

Description:

UV CURING. Special LED lamps for quick curing of UV-curing primers, fillers, paints and also adhesives

Flexible cordless LED hand-held lamp for UV curing of small and medium-sized areas. Curing area Ø

10 cm. Supplied with charging station, Li-ion battery (2.6 Ah).

**Rechargeable UV Work Lamp** 

IP30: Protected against penetration by foreign bodies with @ > 2.5 mm, however tools and wires

should be kept away, and offers no protection against water.

Article No.	UV Radiation	Working Life	Battery Capacity	Battery Voltage	Size (mm)
#S#12821	390nm	1.5h	2.6 A.h	3.7V	190mm





#### INDUSTRIAL SOURCING SOLUTIONS CO.

INNOV/TION FROM

Description: UV CURING. Special LED lamps for quick curing of UV-curing primers, fillers, paints and also

adhesives.

Rechargeable floodlight for UV curing of large areas. Curing area Ø 20 cm. Supplied with charger, Liion battery (5.4 Ah), integral power bank with USB port.

IP30: Protected against penetration by foreign bodies with Ø > 2.5 mm, however tools and wires

**Rechargeable UV Work Lamp** 

should be kept away, and offers no protection against water.



LED

IP30

**IP67** 

IP65

IP65

LED

LED



Article No.	UV Radiation	Working Life	Battery Capacity	Battery Voltage	Size (mm)
#S#12822	390-400nm	1.5h	5.4 A.h	3.7V	163mm

#### (SCANGRIP

## Rechargeable True Colour Work Lamp

Description:

COLOUR MATCH. Special LED with high CRI value for perfect colour reproduction and extremely long LED working life. Perfect for all painting, polishing, cleaning and preparation work. Designed for use in paint shops. Exchangeable glass lens and resistant to all types of solvent, even when cleaned every day.

MULTIMATCH 3. Powerful portable cordless work light with selector switch for 5 colour temperatures. Display at the back, showing the battery capacity and remaining working time. Integral adjustment base for direct mounting on Scangrip stand.

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Including battery charger.

	Article No.	Illumination	Working Life	Size (mm)	Weight	Battery Capacity	Battery Voltage
#S#12828 3000 15n 240X230 1970g 4 A.n 11.1V		3000	15h	240x230	1970a	4 A.h	11.1V

#### (SCANGRIP<sup>®</sup>

#### Rechargeable True Colour Work Lamp

Description:

COLOUR MATCH. Special LED with high CRI value for perfect colour reproduction and extremely long LED working life. Perfect for all painting, polishing, cleaning and preparation work. Designed for use in paint shops. Exchangeable glass lens and resistant to all types of solvent, even when cleaned every day.

MINIMATCH. With a 2 COLOUR LIGHT function. This allows the choice between two colour temperatures depending on the work in hand. Warm light (4500 K) for light surfaces and cold light (6500 K) for dark surfaces.

Rechargeable dust-proof and waterproof cordless hand-held work lamp. With sturdy swivel hook and powerful built-in magnet. Flexible lamp head (swings through180°).

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with charger and USB cable.

Article No.	Illumination	Working Life	Size (mm)	Weight	Battery Capacity	Battery Voltage
#S#12826	200	2h	156x60	190g	1.6 A.h	3.7V



#### SCANGRIP Rechargeable True Colour Work Lamp

Description:

COLOUR MATCH. Special LED with high CRI value for perfect colour reproduction and extremely long LED working life. Perfect for all painting, polishing, cleaning and preparation work. Designed for use in paint shops. Exchangeable glass lens and resistant to all types of solvent, even when cleaned every day.

SUNMATCH 3. Cordless LED hand-held work lamp with selector switch for 5 colour temperatures (ALL DAYLIGHT function).

Rechargeable dust-proof and waterproof cordless hand-held work lamp. With sturdy swivel hook and powerful built-in magnet. Flexible lamp head (swings through180°).

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with charger and USB cable.

Article No.	Illumination	Working Life	Size (mm)	Weight	Battery Capacity	Battery Voltage
#S#12827	500	4h	190x60	270g	2.6 A.h	3.7V



## LAMPS & ELECTRICAL ACCESSORIES

IP54

LED

#### **(**SCANGRIP<sup>®</sup> **True Colour Pen Torch**

## Description:

COLOUR MATCH. Special LED with high CRI value for perfect colour reproduction and extremely long LED working life. Perfect for all painting, polishing, cleaning and preparation work. Designed for use in paint shops. Exchangeable glass lens and resistant to all types of solvent, even when cleaned everv dav.

MATCHPEN. Small portable pen torch with focus function for bundled and concentrated illumination between 10° and 70°. Ideal for detecting scratches and scuffs during quality control. IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.



18 Watts

IP54

LED

Supplied with  $2 \times AAA$  batteries. Article No. Illumination Working Life Size (mm) Weight

#S#12825	100	2h	150x16	60g					
CRI value (> 95 IP54: Protected into the inside (p	True Colour P with focussable lamp i) for recognition of d against splashed w protected against du × AAA batteries.	o head, pocket clip a colour matching. rater from all directio	ons and protect	ed against pen	-	IP54	LED		[] ] HOLEX. [[enn teast case mans]]
Article No. #S#12824 THEONE	Illumination 100 M	Working Life 2h	Size (mm) 135x17	Weight 60g		IP66	LED	130 Watts	
Infrared board of Surge Protectio Luminous Flux = Colour = 6500K Input voltage 10 Power input 130	= 18000lm (1W = 13 00~240V 50Hz~60H 0Watts rature 80 degree	etal core (PCB) 33 ti 38lm)	mes better.				1 1		

Article No. Size (mm) #S#00683 300x200x100

#### (SCANGRIP

#### **Rechargeable Floodlight** Description:

Non-shadowing and non-dazzle version with wide spread of light. With 2 lighting levels and up to 3 hours illumination. Base of steel, powder-coated

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching. Voltage 220V - 240V

Article No.	Illumination	Siz (LxWxH)	Weight
#S#12968	4000	305x199x199	3500g

## Cordless Rod Lamp

Description:

# The Line Light work lamp is formed of an extruded acrylic profile with an integral lens (beam dispersion angle 75°). It is thus exceptionally sturdy and shock-resistant. The lamp can be rotated in its housing to give lighting without dazzle. It is thus designed for use under the harshest conditions

and reliably provides strong and concentrated light in any working area.

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Application: With battery for mobile use with additional torch on the end (150 Lumen).

Supplied with: Work light with battery, charger, mounting clip with magnet, and lockable hook. Separately switchable floodlight and torch.

Article No.	Illumination	Working Life	Size (mm)	Colour
#S#12973	150-400	1.5h	Ø25X380L	6000K



Afficie No.	illumination	working Life	Size (mm)	Colour	
#S#12973	150-400	1.5h	Ø25X380L	6000K	
SCANGRIP					
INNOVATION FROM DENMARK	Pen Torch				IP54 LED
Description:	at LED torch of all	minium with bandy	rotainar clin far pr	ofossional uso	
	ight beam from 10	uminium, with handy -60° spread			
	ight boain noin ro	oo oproud.			« (SCANGRIP
unction:				1	
	•	ater from all direction	ons and	and the	
•	penetration of due				
protected agains	t dust), also comp	letely protected aga	inst touching.	E?	
				(K)	
Article No.	Illumination	Working Life	Size (mm)		
#S#12975	100-200	1.75h-3.5h	Ø16x153L		
<b>Å</b> Garant <sup>*</sup>					
	Pen Torch				IPX40 LED
Description: .ong-life and very	sturdy LED torch	of anodised alumin	ium. Latest 1 Watt	or 3 Watt LED technology	
vith outstanding li	-				
•	little scatter loss.				
	ciency for long illu				
•	easy to find in the				
Splash-proof, pr witch at rear.	otection class IPX	.4.			
	against splashed w	ater from all direction	ons, but without any	y protection against foreign	
odies or touching	•		, but minout dry		
upplied with: Inc	•				
Article No.	Illumination	Working Life	Sizo (mm)		
Article No. #S#12977	Illumination 35	4h	<u>Size (mm)</u> Ø16x140L		
HOLEX	Pen Torch				
escription:					IP54 LED
			indled and concent	rated illumination between	
	tical pocket clip a		no and protocted	aningt nonstration of during	
	•	ater from all direction as the second s	•	against penetration of dust	
to the mode (pro	olocieu ayamsi ul	iso, also completely	protected against	touoning.	HOLEX./ourvau
Article No.	Illumination	Working Life	Sizo (mm)		
Article No. #S#12823	Illumination 120	<u>Working Life</u> 6h	Size (mm) Ø17x130L		
	.20		2		
LEDLENSER	Torch Light				
escription:	. s. s. Eight				IP54 LED
ompact torches	in bar format or ke				
ptionally as a dis	sposable battery o	or rechargeable batt	ery version.		
FD lenses are a	monast the techno	logy leaders for I E	D torches Within t	he splash-proof aluminium	• LEDLERSER PI
				ht uniformly and without	1.5
sses.					
			<b></b>	_	
Article No. #S#15651	Illumination	Working Life	Size (mm)	Туре	
#S#15651 #S#15652	25 140/20	6h 2.5h/6h	Ø19x90L Ø20x102L	A A (Rechargeable)	● LEOLEFSER PA 留
#S#15653	120/10	4h/20h	Ø15x140L	B	
#\$#15654	120/10	4h/18h	Ø15x146	B (Rechargeable)	- 🗥 . т

#S#15654

120/10

4h/18h

Ø15x146L

B (Rechargeable)

#### INDUSTRIAL SOURCING SOLUTIONS CO.

IP67

IP67

LED

LED

## LEDLENSER Torch Light - Rechargeable

Description:

LED lenses are amongst the technology leaders for LED torches. Within the splash-proof aluminium housing, all the contacts are gold-plated, high-quality lenses gather the light uniformly and without losses.

- Core series LED lenses, the new generation of the well-known P series.
- Dimmable
- Extremely good protection against dust and water index of protection IP68.
- Easy battery charging using the Magnetic Charge System.

Article No.	Illumination	Working Life	Size (mm)
#S#15655	320/20	1h/12h	Ø30x125L
#S#15656	450/200/20	1.75h/3.5h/30h	Ø35x148L

## 

#### Torch Light (Rubber Cover) - Rechargeable

Description:

LED lenses are amongst the technology leaders for LED torches. Within the splash-proof aluminium housing, all the contacts are gold-plated, high-quality lenses gather the light uniformly and without losses.

Work series LED lenses, virtually indestructible lamps for use in the rough industrial environment. - Rubber covering around the lamp head and on the end cap provide protection against impacts and damage.

- Additional front screen protects the lens against scratches.

Article No.	Illumination	Working Life	Size (mm)	Туре
#S#15657	900/400/50	0.75h/2h/15h	Ø43x162L	А
#S#15658	2500/600/50	1h/5h/60h	Ø96x182L	В









Description:

High-quality, long-life and sturdy LED torch of anodised aluminium. Latest LED technology with outstanding lighting power.

- Anti-roll protection.

- Rubber cover for the operating button.

#### With focussable lamp head.

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Article No.	Illumination	Working Life	Size (mm)
#S#14260	35	7h	94L
#S#15650	160	5h	117L
#S#12982	250	9h	160L







## Torch Light

Description: High-quality, long-life and sturdy LED torch of anodised aluminium. Latest LED technology with outstanding lighting power.

- Anti-roll protection.

- Rubber cover for the operating button.

With focussable lamp head. In various colours.

Article No.	Illumination	Working Life	Size (mm)	Colour
#S#04772	250/100	4h/12h	Ø27x143L	Black
#S#04775	250/100	4h/12h	Ø27x143L	Silver
#S#04773	250/100	4h/12h	Ø27x143L	Grey
#S#04774	250/100	4h/12h	Ø27x143L	Red





LED

#### **Ex Protection Torch Light**

• LEDLENSER Description:

 $\label{eq:explosion-proof torch, tested to the applicable ATEX guidelines.$ 

The lamps of the new LED Lens EX series are certified both for maximum dustproof and waterproof qualities.

Handy lightweight pen torch, with pressure switch.

Function:

IP68: Protected against continuous submersion in water (watertight) and protected against penetration by dust (dust-tight), also completely protected against touching.

EX4 CLEDLENSER	Type A
	Type B

ATEX

Article No.	Illumination	Working Life	Size (mm)	ATEX Zone	Туре
#S#12984	50	7h	Ø20x140L	Zone 0; Zone 20	A
#S#12985	60-200	16h-45h	Ø41x161L	Zone 0; Zone 20	В

<b>Underwate</b> Kinetics							
Description:	Ex Protection	Torch Light			IP67	LED	ATEX
	f torch, tested to the	applicable ATEV a	uidelinee				
	with impact resistar						
•	en torch of the lates	•	•	vitab at roor			
		si generation with po	ocket clip and sv	Alch al lear.			1
							( Jacobs
Article No.	Illumination	Working Life	Size (mm)	ATEX Zone			
#S#12986	35	3h	Ø22x132L	Zone 1; Zone 21			
		2.1					
<b>II</b> Underwater	r						
<b>UN</b> Kinetics	Ex Protection	Torch Light			IP67	LED	ATEX
Description:		-					
Explosion-proof	f torch, tested to the	applicable ATEX g	uidelines.				
Special torch wi	ith impact resistant a	and waterproof ABS	casing.		6		
With LED reflect	ctor technology.				(K)-		
					× .		
LED hand-lamp	and helmet lamp w	ith bright spot beam	n, flame-resistan	t to EN 443, TRS system for	2 =		
	and helmet lamp w prmance at temperat			t to EN 443, TRS system for			
				t to EN 443, TRS system for	J.		
				to EN 443, TRS system for	Į.		

Focussable LED hand-lamp and helmet lamp (light beam 13° - 22°), 2 power settings (high / low), patented lens system, front switch.

Article No.	Illumination	Working Life	Size (mm)	ATEX Zone	
#S#12988	230	5h	Ø35x170L	Zone 0; Zone 20	

LED safety lamp with smooth wide-angle beam, ideal for lighting larger areas, helmet mount for easy attachment to work helmets and safety helmets.

Article No.	Illumination	Working Life	Size (mm)	ATEX Zone
#S#12989	225	6.5h	Ø35x158L	Zone 0; Zone 20

Twin-beam LED safety lamp, front switch for the primary beam (shines forwards), rotary knob switch for the secondary beam (shines downwards), no reduction in the working duration if the two beams are used at the same time.





Article No.	Illumination	Working Life	Size (mm)	ATEX Zone	
#S#12990	170/20	6.5h	Ø35x158L	Zone 0; Zone 20	





LED

#### 

#### Description:

Innovative LED work headlamp with wide spread of light for optimum illumination of the entire work area. Light-weight slim profile lamp. Non-contact switching on and off, thanks to sensor system with two lighting levels.

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Supplied with USB charger.

Article No.	Illumination	Working Life	Weight (g)
#S#12991	125-250	3h-6h	240



#### 

Description:

Powerful high-performance LED industrial headlamp for professional use.

- Pivoting head and stepless focussing function.

- Exchangeable and washable head band.

Very light-weight headband lamp, easy to operate. Easily dimmed.

Article No.	Illumination	Working Life	Weight (g)
#S#15659	120/5	6h/60h	133

Innovative multi-purpose light with removable lamp head.

Flexibility in use, can be operated either with a rechargeable battery or disposable battery.

Article No.	Illumination	Working Life	Weight (g)
#S#15660	200/20	4.5h/35h	92





## Headlamp - Rechargeable

Description: LED work headlamp with wide spread of light for optimum illumination of the entire work area. Noncontact switching on and off, thanks to sensor system with 2 lighting levels. IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching. Supplied with battery charger.

Article No.	Illumination	Working Life	Weight (g)
#S#15661	100/300	6h/2h	111





<b>Vinderwate</b>
Mimohioo

### **INKinetics** Ex Protection Headlamp

Description: Explosion-proof headband lamp, tested to the applicable ATEX guidelines.

Surface, lightweight LED headband lamp with detachable lamp module for use as a work lamp. 3 selectable beam profiles (point, diffused, diffused red), 2 light intensities (high / low), non-slip rubber helmet strap (textile strap available as an option).

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with batteries – (3× AAA).

Article No.	Illumination	Working Life	Weight (g)
#S#12997	35-65	13h-17h	110





LED

#### **Ex Protection Headlamp**

Description:

Explosion-proof headband lamp, tested to the applicable ATEX guidelines. Headband lamp, very comfortable to wear, focussable, with red backlight. Comfortable "Magnetic Switch" for easy operation even when wearing gloves and protective equipment. Comfortable "Magnetic Switch" for easy operation even when wearing gloves and protective equipment.

Headlamp, very comfortable to wear, focussable, with red backlight.

IP68: Protected against continuous submersion in water (watertight) and protected against penetration by dust (dust-tight), also completely protected against touching. Supplied with batteries (3 × AA).

Article No.	Illumination	Working Life	Weight (g)
#S#12998	180/50	15h/40h	345



ATEX



## Workstation Lamp

Description:

High quality, universally usable lamps for 250 V / 50 Hz with On / Off switch, 3 m rubber connection cable.

Robust, long, coated flexible metal arm for good mobility of the lamp head and high stability. 20 or 50 Watt halogen flood beam with reflector.

IP20: Protected against penetration by foreign bodies with  $\emptyset < 12$  mm, however touching should be avoided, and offers no protection against water.

Supplied with:

Bulb, with strong magnetic clamp, 50 mm screw-on clamp, and mounting screws for machine, table, wall or ceiling attachment.

Article No.	Illumination	Power	Colour	Cable	
#S#13406	420	50W	3000	3 m	

High quality, universally usable lamps for 250 V / 50 Hz with On / Off switch, 3 m rubber connection cable. Robust, long, coated flexible metal arm for good mobility of the lamp head and high stability. Can be switched from flood to spot beam, lamp head can be turned and swivelled 340° using the ball joint.

Article No.	Illumination	Power	Colour	Cable
#S#13407	780	50W	3000	3 m









## Workstation Lamp

Description:

High quality, universally usable lamps for 250 V / 50 Hz with On / Off switch, 3 m rubber connection cable.


Robust, long, coated flexible metal arm for good mobility of the lamp head and high stability. Machine lamp with LEDs for directed illumination of the workplace. Low power consumption, avoids heating up the illuminated objects and subjecting them to UV radiation.

IP20: Protected against penetration by foreign bodies with ø < 12 mm, however touching should be avoided, and offers no protection against water.

#### Supplied with:

Bulb, with strong magnetic clamp, 50 mm screw-on clamp, and mounting screws for machine, table, wall or ceiling attachment.

Article No.	Illumination	Power	Colour	Cable	No. LED
#S#09541	450	6W	6500	3 m	4









## brennenstuhl Smoke Detector

Description: In the presence of smoke reliably raises the alarm with a shrill sound (85 dB). VDS certified. 10 year working life using the permanently-installed 3 V lithium battery. No need to change the

Note: Smoke detectors must be replaced after 10 years operation.

Article No.	Alarm Volume	Size (mm)
#S#13260	85dB	Ø100x31H

#### Adapter Plug For Power Tools - GB

Description: Adapter for connecting shock-proof plugs (3 pin plugs) with other European plug systems. Positive adapter plug for power tools.

Suitable for: Great Britain

Voltage : 250

battery.

Article No. #S#00903



#### Adapter Plug With Earth Contact - GB

Description:

Adapter for connecting shock-proof plugs (3 pin plugs) with other European plug systems. 3-pin adapter plug, e. g. for measuring machines.

Suitable for: Great Britain

Voltage : 250



#### Article No. #S#03430

#0#00400

## **Å** Garant\*



Description: Cable reel with guided automatic draw-in and roll-up, with multiple stop points per revolution. Highimpact enclosed plastic housing. Thermal overload cut-out, sturdy H07RN-F neoprene cable with connection point.

Easy to mount on the wall or ceiling, with 180° pivoting range.

Function:

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with  $\emptyset > 1$  mm, however tools and wires should be kept away.

#### Application:

Improved ergonomics by relieving cable tension, and for ensuring tidiness and avoiding the risk of accidents and injuries due to cables lying on the ground.

Rated power unrolled : 2400 W Nominal voltage : 250 V Material cable : Neoprene Length : 496 mm Width : 192 mm Height : 401 mm

Attention: German version

Cable Length
15 Meter









Safety Cable Reel

Description: Cable reel with guided automatic draw-in and roll-up, with multiple stop points per revolution. Highimpact enclosed plastic housing. Thermal overload cut-out, sturdy H07RN-F neoprene cable with connection point.

Easy to mount on the wall or ceiling, with 180° pivoting range.

Function:

EJN

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with Ø > 1 mm, however tools and wires should be kept away.

Application:

Improved ergonomics by relieving cable tension, and for ensuring tidiness and avoiding the risk of accidents and injuries due to cables lying on the ground.

Rated power unrolled : 2400 W Nominal voltage : 250 V Material cable : Neoprene Length : 490 mm Width: 190 mm Height: 410 mm

Attention: German version

Article No. **Cable Length** #S#07254 17 Meter



## Cable Reel - 400V

Cable reel with guided automatic draw-in and roll-up, with multiple stop points per revolution. Highimpact enclosed plastic housing. Thermal overload cut-out, sturdy H07RN-F neoprene cable with connection point.

Easy to mount on the wall or ceiling, with 150° pivoting range.

Application:

Improved ergonomics by relieving cable tension, and for ensuring tidiness and avoiding the risk of accidents and injuries due to cables lying on the ground.

Nominal voltage : 400 V Material cable : Neoprene Length : 361 mm Width : 208 mm Height : 450 mm

Attention: German version

Article No.	Cable Length	Rated power unrolled
#S#07255	15 Meter	5000 (16A) W
#S#07256	20 Meter	3000 (16A) W



## Extension cable - 400V

Certified for exterior use and for use in humid environments (IP44). Neoprene rubber cable H07RN-F 5G1.5 resistant to oil, petrol and UV radiation.

Function<sup>-</sup>

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with Ø > 1 mm, however tools and wires should be kept away.

AC supply voltage : 400 V

Attention: German version







Cable Length Article No. #S#13263 10 Meter

